

85-SSH

Recessed Plaster Frame (NON-IC)


Static or Selectable Wattage/CCT

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

SPECIFICATIONS

- HOUSING — 14-gauge aluminum, die formed, welded construction.
- DOOR FRAME — 14-gauge aluminum, die formed.
- PLASTER FRAME — 16-gauge galvanized steel, die formed.
- LENS — 5/32" (0.156") thick, prismatic polycarbonate.
- LENS FASTENERS — 14-gauge, die formed aluminum. Secured in place by hex nuts.
- GASKETS — Door frame and lens incorporate gasket.
- DRIVER — Universal voltage (120-277V) electronic driver with 0-10V dimming is standard.
- LIGHT ENGINE — Energy efficient LED - Static or Selectable Wattage/CCT. Minimum of 80 CRI.
- FINISH — Baked and cured polyester powder coat finish. (SKW) Sky White finish standard.
- MOUNTING — Lay-in plaster frame installs into a 13-1/4" square ceiling opening. Housing installs into plaster frame with two point lock up into plaster frame. Door frame secured to housing via four point security lockup and seals luminaire to ceiling surface. Three 3/4" trade and two 1/2" trade knockouts provided on top of housing for line side power.
- COMPLIANCE — Designed and built to U.S. and Canadian Safety Standards. Complies with Buy American Act and Buy America Compliant. Suitable for wet, damp and dry locations with covered ceilings. Not for use in insulated ceilings.



ORDERING INFO

Series	Wattage	CCT	Voltage	Finish	Options

ORDERING GUIDE:

SERIES

85-SSH = 85 Super Shallow Series

WATTAGE

LED25 = 25 Watt LED

LED30 = 30 Watt LED

LED40 = 40 Watt LED

SLED = *Selectable Wattage: 13.5W | 17W | 20.5W
— See Chart Below for Lumen Output

COLOR TEMPERATURE (CCT)

3K = ±3000K range LED

35K = ±3500K range LED

4K = ±4000K range LED

5K = ±5000K range LED

SCCT = *Selectable CCT: 3000K | 3500K | 4000K | 5000K
— Compatible with SLED Only

VOLTAGE

UNV = Universal Volt (120-277v) Electronic Driver

*Note: Fixtures will ship from factory at lowest wattage and warmest CCT. It is the installer's responsibility to set the fixture at the desired wattage and CCT for their project.

STANDARD FINISH

BK = Black Finish

BZ = Bronze Finish

PNA = Painted Natural Aluminum

SKW = Sky White Finish

WH = White Finish

LENS OPTIONS

81 = .156" Prismatic Polycarbonate

98 = .118" Frosted Polycarb. / Glare Control

CONTROL OPTIONS

MANUAL CONTROL (Wall Switch or Control System)

Note: 0-10V 100%-30% is Standard

D7A = 0-10VDC LED Dimming Driver (100-10%)

D7B = 0-10VDC LED Dimming Driver (100-1%)

BLS = Bi-Level Switching (Includes Two Drivers)

OR

Sensor Control (Sensor Integral to Fixture)

OCC = Occupancy Sensing | Motion Sensor Integral[Ⓜ]

— Microwave / Single Feed / 120/277V Only

— Standby Dim Level Presets: ON/OFF (0%/100%)

BLD = Bi-Level Dimming | Motion Sensor Integral[Ⓜ]

— Microwave / Single Feed / 120/277V Only

— Standby Dim Level Presets:

10% / 20% / 30% (Standard) / 50%

EMERGENCY BATTERY OPTIONS[Ⓟ]

Meets California Energy Commission Title 20:

(CEC-400-2014-009-CMF) Efficiency Standards

EL10W = Integral LED 10 Watt

Cold Weather Emergency Batteries:

Operating Temp: -20°C thru 50°C / NON-CEC Compliant

EL10W-CW = Integral LED 10 Watt (Cold Weather)

ACCESSORY OPTIONS (order as a separate line)

9002 = Tamperproof Screwdriver

NOTES:

[Ⓜ] Max mounting height of fixture is 18' (18 feet)

[Ⓟ] Final selection of the Battery Pack under discretion of Factory

Selectable Wattage	3000K	3500K	4000K	5000K
13.5W	2,100 Lumens	2,125 Lumens	2,150 Lumens	2,200 Lumens
17W	2,650 Lumens	2,675 Lumens	2,700 Lumens	2,750 Lumens
20.5W	3,100 Lumens	3,125 Lumens	3,150 Lumens	3,200 Lumens

85-SSH

Recessed Plaster Frame (NON-IC)

Static or Selectable Wattage/CCT

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

DIMENSIONS

