

# SRF Series

## Vandal Resistant Canopy Fixture

### Semi-Recessed - Flat Polycarbonate Lens

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

#### SPECIFICATIONS

- APPLICATIONS— Eaves, Breezeways, Canopy, Soffit, Stairwell.
- DRIVER— Universal voltage (120-277v) electronic driver with 0-10V dimming.
- FINISH — Backplate and Frame are Phosphate pre-treated and finished in Oven Baked White Polyester Powder Coat.
- LIGHT ENGINE — Energy efficient Light Emitting Diode (LED).
- LENS — #80 Flat 1/8" Thick (.125) Prismatic Polycarbonate is standard.
- LENS FASTENERS — Four (4) Stainless Steel Torx Tamperproof Screws to Secure Frame to Backplate.
- MOUNTING — Standard Semi-Recessed Mounting.
- COMPLIANCE — Built to comply with U.S. and Canadian safety standards. Suitable for Damp Locations — Retrofit Electric Lighting Fixture. **Made in USA / Buy America Compliant / Buy American Act.**



ORDERING GUIDE:	Series	Size	LED Wattage	CCT	Voltage	Finish	Options
-----------------	--------	------	-------------	-----	---------	--------	---------

#### SERIES

SRF = SRF Series

#### SIZE

- M = 13-1/2" Square (7-3/4" Sq Opening)
- L = 15-1/2" Square (10-3/4" Sq Opening)
- XL = 19" Square (10-3/4" Sq Opening)

#### LED WATTAGE

- LED30 = LED 30 Watt
- LED40 = LED 40 Watt (Size X-Large Only)

#### LED COLOR TEMPERATURE (CCT)

- 3K = ±3000K range LED
- 4K = ±4000K range LED
- 5K = ±5000K range LED

#### VOLTAGE

- 347 = 347 Volts
- UNV = Universal Volt (120-277v) Driver

#### FINISH

- BK = Black Finish
- BZ = Bronze Finish
- PNA = Painted Natural Aluminum
- SGR = Silver Gray
- WH = White Finish - STANDARD
- CC = Custom Color (Visit [www.ralcolor.com](http://www.ralcolor.com))  
— Provide RAL# or Make-to-Match Color Chip

#### LENS OPTIONS

- 81 = .156" K12 Prismatic Polycarbonate (flat lens)

#### DIMMING OPTIONS

Note: 0-10V 100%-30% is Standard

- D7A = 0-10VDC LED Dimming Driver (100-10%)
- D7B = 0-10VDC LED Dimming Driver (100-1%)

#### EMERGENCY OPTIONS<sup>50 55</sup>

**No onsite Emergency Power (AC or DC) is provided**

**Meets California Energy Commission Title 20:**  
(CEC-400-2014-009-CMF) Efficiency Standards

- REL4W = Remote LED 4 Watt
- REL8W = Remote LED 8 Watt
- REL16W = Remote LED 16 Watt
- REL20W = Remote LED 20 Watt

#### Cold Weather Emergency Batteries:

Operating Temp: -20°C thru 50°C  
NON-CEC Compliant

- REL10W-CW = Remote LED 10 Watt (Cold Weather)
- REL23W-CW = Remote LED 23 Watt (Cold Weather)

#### ACCESSORY OPTIONS (order as a separate line)

- 9002 = Tamperproof Screwdriver
- SRF-NE = Non-electrical to cover a recessed opening and re-use existing electrical components.

<sup>50</sup> Max WHIP length of the REL is 8 feet.

<sup>55</sup> Final selection of the Battery Pack under discretion of Factory

#### DIMENSIONS

