

# Mini R9

## Indoor Mini Drum Fixture Ceiling or Wall Family—Damp Location ADA Compliant

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

### SPECIFICATIONS

- DRIVER — 120V or 277V Electronic Driver.
- DIFFUSER — Opal Acrylic Standard.
- EMERGENCY — LED— Integral Emergency Battery.
- FINISH — Brushed Nickel, Bronze, or White Polyurethane Finish.
- LED — Energy Efficient Light Emitting Diode (LED).
- MOUNTING — Ceiling or Wall Mount.
- COMPLIANCE — Built to comply with U.S. and Canadian safety standards.  
Suitable for damp locations. (Covered Ceiling Only)



Mini R9 Wall Mount



Mini R9 with Back Box Wall Mount



Mini R9 Ceiling Mount



Mini R9 with Back Box Ceiling Mount



Mini R9 shown with Back Box and Battery Indicator/Button

**ORDERING GUIDE:**

Series	Mounting	Lamp/Wattage	Color Temp	Voltage	Finish	Options
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

#### SERIES

MR9 = Mini R9 Series

#### MOUNTING

CM = Ceiling Mount  
WM = Wall Mount

#### LAMP-TYPE/QUANTITY/WATTAGE

LED18 = 18 Watt Light Emitting Diode

#### VOLTAGE

120 = 120 Volts  
277 = 277 Volts (White Finish Only)

#### LED COLOR TEMPERATURE

27K = ±2700K range  
3K = ±3000K range  
5K = ±5000K range

#### FINISH

BN = Brushed Nickel Finish  
BZ = Bronze Finish  
WH = White Finish

#### OPTIONS

BB = Back Box

#### LED EMERGENCY OPTIONS

*No onsite Emergency Power (AC or DC) is provided*  
Specify Fixture Voltage: 120V or 277V Power Feed  
A=120V or B=277V

EL = Integral LED Emergency Battery (Consult Factory)

Tested in accordance with LM-79-80  
 The results contained in this summary report pertain only to the tested sample

Summary of Results		
Total Lumen Output	1258.5 Lumens	
Efficacy (Lm/W)	68.0 Lm/W	
Wattage	18.5W	
Color Temperature	2700K	
Test Temperature	25°C (±1°C)	
Voltage	120	
Bug Rating	B1-Ux-G1	
Zonal Lumen Summary		
Zone	Lumens	% Luminaire
0-30	369.4	29.4
0-40	604.0	48.0
0-60	1049.7	83.4
60-90	208.8	16.6
0-90	1258.5	100.0

