

# Liverpool 5

Full Cutoff Wall Pack Luminaire  
Selectable Wattage / CCT  
Wet Location / IP65 Rated

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

## SPECIFICATIONS

- DRIVER — Universal Voltage (120-277v) electronic driver with 0-10V dimming.
- HOUSING — Die-cast aluminum with built-in heatsink, fully sealed by silicone ring that prevents dust and other contaminants from entering.
- FINISH — Polyester powder coated finish.
- LENS — U.V. stabilized polycarbonate lens for uniform illumination.
- LIGHT ENGINE — Energy efficient LED featuring Selectable Wattage/CCT.
- LIFETIME — 50,000+ Hour LED Life Expectancy (L70).
- MOUNTING — Mounts to standard 4" J-BOX.
- OPERATIONAL TEMP — -40°F to +113°F.
- PHOTOCELL — Photocell is standard.
- COMPLIANCE — Built to comply with U.S. and Canadian Safety Standards.  
DLC 5.1 Compliant. UL listed for Wet Location, IP65 Rated.
- WARRANTY — 5-Year Limited Warranty.



## ORDERING INFO

	Series	Wattage	CCT	Voltage	Finish	Options
ORDERING GUIDE:						

### SERIES

LV5 = Liverpool 5 Series

### WATTAGE

Note: Refer to Below Chart for Wattage / Lumen Output  
SLED-L = \*Selectable Wattage - Low: 40W | 60W | 80W  
SLED-H = \*Selectable Wattage - High: 80W | 100W | 120W

### COLOR TEMPERATURE (CCT)

SCCT = \*Selectable CCT: 3000K | 4000K | 5000K

\*Note: Fixtures will ship from factory at lowest wattage and warmest CCT. It is the installer's responsibility to set the fixture at the desired wattage and CCT for their project.

### VOLTAGE

UNV = Universal Volt (120-277v) Driver

### STANDARD FINISH

BZ = Bronze Finish

### PREMIUM UPCHARGE FINISHES

BK = Black Finish  
PNA = Painted Natural Aluminum  
WH = White Finish

SLED Model	SLED-L			SLED-H		
Wattage	40W	60W	80W	80W	100W	120W
Lumens	5,200	7,800	10,400	10,400	13,000	15,600

## DIMENSIONS

