

# Sonic 3

## Round Surface Mount Disc with Night Light Selectable 5CCT / Dimmable Ceiling or Wall / Damp Location

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

### SPECIFICATIONS

- DRIVER — 120V electronic driver with low voltage dimming (100-10%).
- DIFFUSER — Poly Methyl Methacrylate (PMMA) diffuser.
- HOUSING — Die-formed cold rolled steel.
- FINISH — Brushed Nickel or Matte Black finish.
- LIGHT ENGINE — Energy Efficient LED with Selectable CCT via integrated switch.  
Standard LED module operates at 90CRI with 120° Beam Angle.
- NIGHT LIGHT — Built-in Night Light which can be operated with intergrated switch.  
Night Light LED operates at 2200K with 100 lumen output.
- OPERATIONAL LIFETIME — 50,000 Hours
- OPERATING TEMP — -20°C to 40°C | -4°F to 104°F
- COMPLIANCE — Built to comply with U.S. and Canadian safety standards.  
Suitable for damp locations.
- WARRANTY — 5-Year Limited Warranty.



### ORDERING INFO

Series	Wattage	CCT	Voltage	Finish	Options

#### ORDERING GUIDE:

##### SERIES

SC3 = Sonic 3 Series

##### WATTAGE

LED26 = 26 Watt LED (1700-2000 Lumens)

##### COLOR TEMPERATURE (CCT)

SCCT = \*Selectable CCT: 2700K | 3000K | 3500K | 4000K | 5000K

*\*Note: Fixtures will ship from factory at warmest CCT. It is the installer's responsibility to set the fixture at the desired wattage and CCT for their project.*

##### VOLTAGE


120 = 120V Electronic Driver

##### STANDARD FINISH

BK = Matte Black

BN = Brushed Nickel

### DIMENSIONS



### LIGHT MODES

### SELECTABLE CCT



Down Light Mode



Night Light Mode



Selectable CCT Switch  
Located on LED Board Module