

# CMK Series

## SMALL BASIC VANDAL RESISTANT Retrofit Cover for Existing Recessed Fixture

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

### SPECIFICATIONS

- APPLICATIONS— Eaves, Breezeways, Canopy, Soffit, Stairwell.
- DRIVER — Universal Voltage (120-277v) Electronic Driver with 0-10V dimming.
- FINISH — Frame is Phosphate Pre-Treated and Finished in Oven Baked White Polyester Powder Coat.
- FRAME — Heavy Gauge Aluminum—Die Formed and Spot Welded Construction.
- LIGHT ENGINE — Energy Efficient Light Emitting Diode (LED).
- LENS — .125" Thick Prismatic Polycarbonate drop pyramidal lens is standard.
- LENS FASTENERS — Heavy gauge Cold Rolled Steel retaining angles attached to thru Door Studs for Positive Lens Clamping.
- MOUNTING — Standard Semi-Recessed Mounting. Allow 4" Depth for SR Box for Driver.
- COMPLIANCE — Built to comply with U.S. and Canadian safety standards. Suitable for Damp Locations—Retrofit Electric Lighting Fixture. **Made in USA / Buy America Compliant / Buy American Act.**
- WARRANTY — Standard 5 Years, defects and workmanship.

\*Consult Factory for Extended Conditional Warranty.



### ORDERING INFO

ORDERING GUIDE:	Series	Size	Wattage	CCT	Voltage	Finish	Options

#### SERIES

CMK = CMK Series  
 CMK-NE = CMK Non-Electrical Series - Cover Only w/Diffuser  
 — Indicate Size as Complete Catalog #  
 Example: CMK-NE-L

#### SIZE (Nominal)

M = Medium - 13-1/2" Square x 3" Depth  
 L = Large - 15-1/2" Square x 3" Depth

#### WATTAGE

LED25 = 25 Watt LED  
 LED35 = 35 Watt LED

#### COLOR TEMPERATURE (CCT)

3K = ±3000K Range LED  
 4K = ±4000K Range LED  
 5K = ±5000K Range LED

#### VOLTAGE

347 = 347 Volts  
 UNV = Universal Volt (120-277v) Driver

#### FINISH

BK = Black Finish  
 BZ = Bronze Finish  
 PNA = Painted Natural Aluminum  
 SGR = Silver Gray  
 WH = White Finish

#### PREMIUM UPCHARGE FINISH

CC = Custom Color (Visit [www.ralcolor.com](http://www.ralcolor.com))  
 — Provide RAL# or Make-to-Match Color Chip

#### DIMMING OPTIONS

Note: 0-10V 100%-30% is Standard  
 D7A = 0-10VDC LED Dimming Driver (100-10%)  
 D7B = 0-10VDC LED Dimming Driver (100-1%)

#### MISC OPTIONS

FUS = Single Fusing

#### EMERGENCY BATTERY OPTIONS<sup>50</sup><sup>51</sup>

**Meets California Energy Commission Title 20:**  
 (CEC-400-2014-009-CMF) Efficiency Standards

REL4W = Remote LED 4 Watt  
 REL8W = Remote LED 8 Watt  
 REL16W = Remote LED 16 Watt  
 REL20W = Remote LED 20 Watt

#### Cold Weather Emergency Batteries:

Operating Temp: -20°C thru 50°C / NON-CEC Compliant

REL10W-CW = Remote LED 10 Watt (Cold Weather)  
 REL23W-CW = Remote LED 23 Watt (Cold Weather)

#### ACCESSORY OPTIONS (order as a separate line)

9002 = Tamperproof Screwdriver

#### NOTES:

- 50 Max WHIP length of the REL is 8 feet.
- 51 Final selection of the Battery Pack under discretion of Factory

### DIMENSIONS

